



Cat.6 FTP 16Port Patch Panel; Cat.6 FTP 24Port Patch Panel, 1U, Shielded

Description

Part Number:
D1-6UHD/F-PP16
D1-6UHD/F-PP24



Features:

Patented:

Easy removable rear shielded cover-PUSH & SQUEEZE to open.

- Higher printed-circuited-board capacity.
- Flexible design (16&24 ports for 1U).
- Our patch panels are made of sturdy, rolled-edge, anodized.
- The panels feature a fully enclosed design for protection of printed circuitry during termination.
- Meet the TIA/EIA-568-B.2-1 Category 6 Channel Testing Performance Requirements.
- Offer total solution of your Local Networking Area.
- Color-coded for T568A and T568B wiring schemes.
- D'ONE Infra Cat.6 panels are design for maximum strength and compatible with standard 110 or Krone Installation tools.
- D'ONE Infra panels Fit and Install in 19 inch cabinet.

Physical Specifications:

- High-density 1U, 19" RMS (rack mount standard) design (16,24 ports). Meet EIA-310-D specifications.
- Apply UL94-V-0 high impact, fire-retardant ABS or PC material.
- A pair punch sequence enables a pair twist within 1/2" of termination.
- Beryllium copper contact: 50~μ gold-plated pins over 100~μ nickel layer.
- Insertion life cycle: 1,000 cycle (minimum) / I.D.C 250 cycle (minimum).
- Operating temperature: -40 OC to +68 OC.
- FCC Part 68, UL® certified.

Application:

Category 6 FTP(Shielded) 16&24Port Patch Panel)

Our patch panels are made of sturdy, rolled-edge, anodized. It is perfect for high-speed image, voice and data transmission.

Applications:

- 1,000 Mbps Gigabit Ethernet (IEEE 802.3Z)
- 622 Mbps ATM
- 155 Mbps ATM
- 100 VG-anyLAN (IEEE 802.12)
- 100 Mbps TP-PMD
- 100 Mbps Fast Ethernet (IEEE 802.3u)
- 100 Mbps CDDI
- 10 Mbps Ethernet (IEEE 802.3)
- 4 Mbps & 16 Mbps Token-Ring (IEEE 802.5)
- ISDN

Record of Recognition

